



Part E



Part C

Camlock Coupling & Adaptors

Camlock Couplings are interchangeable with all products manufactured to MIL C 27487 / A-A-59326. The coupling connection is sealed by the folding of two external handles which compress the male part (Part E) against the internal seal within the female part (Part C).

Camlock adaptors are supplied with BSP thread as standard, NPT threads are available as an option.

OPTIONS:

Flanged adaptors, elbow fabrications, reducers, 'Y' pieces, 'T' pieces.

SPARES:

Replacement handles, gaskets, chains and rings.

PRESSURE RATING: 10 Bar working pressure

MATERIALS:

Aluminium
 Stainless Steel
 Brass
 Polypropylene

| Sizes (inch) | Aluminium | Stainless Steel | Brass | Polypropylene |
|--------------|-----------|-----------------|-------|---------------|
| ½ | ✓ | ✓ | ✓ | ✓ |
| ¾ | ✓ | ✓ | ✓ | ✓ |
| 1 | ✓ | ✓ | ✓ | ✓ |
| 1 ¼ | ✓ | ✓ | ✓ | ✓ |
| 1 ½ | ✓ | ✓ | ✓ | ✓ |
| 2 ½ | ✓ | ✓ | ✓ | ✓ |
| 3 | ✓ | ✓ | ✓ | ✓ |
| 4 | ✓ | ✓ | ✓ | ✓ |
| 5 | ✓ | ✓ | ✓ | |
| 6 | ✓ | ✓ | ✓ | |
| 7 | ✓ | | | |
| 8 | ✓ | | | |

CAMLOCK ADAPTORS



Elbow



Type A (BSPP)



Type B (BSPT)



Y Piece



T Piece



Type F (BSPT)



Type D (BSPP)



Dust Caps (Parts DC) and plugs (DP) should not be used in pressure applications