



## Elite PU Type 2 Fire Hose

Our Elite PU supercoated fire hose is complies with BS 6391 Type 2 and other international standards. The hose is a two-component system consisting of a black SBR synthetic rubber inner lining and a synthetic polyester outer jacket, bonded together with NBR-synthetic adhesive. The hose is finally colour coated in a variety of colour options and given a polyurethane surface increasing the abrasion resistance.

### HOSE JACKET

The hose jacket is a 100% polyester high tenacity yarn with circular woven, warp threads 2 ply twisted, plain weave. Standard colour red or blue.

### HOSE LINING

The hose lining and cover is a two-component system consisting of a black SBR synthetic rubber inner lining and a synthetic polyester outer jacket, bonded together with NBR-synthetic adhesive. Externally colour and polyurethane coated. Resistant to ozone and to external contact with oil products. The lining guarantees a smooth surface and low friction loss.

### COUPLING

BS336 Instantaneous, Storz or all international coupling types wired-in for safety & security, with 1.6mm Stainless Steel wire.

### STANDARDS

BS 6391 Type 2 (45 bar) and many other International Standards.

### LENGTHS

Standard and non-standard lengths up to 100 metres. Maximum loose hose length 300 metres made to order. Max change in length 3%, max change in diameter 3%.

### CHARACTERISTICS


- Produced with very low twist.
- Good abrasion resistance and long service life.
- External resistance to oil, fuel and chemical products, low friction loss.
- Ageing and ozone resistant - weather resistant.
- Lightweight and flexible - kink resistant.
- Minimum maintenance and easy to clean.
- Cold resistant to - 30 °C.
- Heat resistant up to + 80 °C.
- Easy to repair - repair material and vulcanizer on request.



Hose Construction: Jacket, NBR-synthetic adhesive and SBR-synthetic rubber



BS Coupling wired in



Standard colours

Internal Diameter		Weight g/m	Burst Pressure bar	Working Pressure Safety Ratio*		Wall Thickness mm
mm	inch			2:1 bar	3:1 bar	
19	¾	130	45	22.5	15	1.40
25	1	150	45	22.5	15	1.40
32	1 ¼	175	45	22.5	15	1.40
38	1 ½	210	45	22.5	15	1.50
42		240	45	22.5	15	1.50
45	1 ¾	250	45	22.5	15	1.50
52	2	300	45	22.5	15	1.60
64	2 ½	400	45	22.5	15	1.60
70	2 ¾	470	45	22.5	15	1.60
75	3	520	45	22.5	15	1.70
90	3 ½	610	30	15	10	1.70
102	4	690	30	15	10	1.80
110	4 ⅓	790	25	13	8	1.80
125	5	910	20	10	7	1.90
152	6	1040	20	10	7	1.90

\*maximum recommended working pressure of the hose, or maximum working pressure of the attached coupling whichever is the lower